

Information User instruction

Safety gloves against chemical risks

Manufacturer

UVEX SAFETY Gloves GmbH & Co. KG
Elso-Klöver-Str. 6, 21337 Lüneburg
Postfach 24 47 · 21314 Lüneburg
GERMANY

Tel.: +49 4131 9502-0
Fax: +49 4131 84338
Email: gloves@uvex.de
Website: uvex-safety.de

Type uvex u-fit
Basic glove material no lining
Available sizes S, M, L, XL

Coating material Material: NBR (nitrile butadiene rubber)
Smallest packing unit 100 Pieces

Pictogram and performance levels

EN 374 : 2003



Pictogram and performance levels according to EN 374:2003
(lowest performance level: 1/highest performance: 6)

The sampling for penetration testing is made by the general inspection level in accordance with DIN 2859, part 1 with AQL 1.5.

Please note: The actual period of protection on the job is affected by many factors (temperature, abrasion, etc.) and can therefore differ from the performance level!

EC notified body SATRA Technology Centre
Wyndham Way, Telford Way, Kettering · NN16 8SD Northamptonshire, United Kingdom
No.: 0321

Cleaning Cleaning only possible when not working with aggressive chemicals. Carefully rinse gloves under lukewarm running water.

Storage Store in a dark, dry place.

Handling Thoroughly check before use for damage. Defective gloves should not be used. All technical data refers to the state of the gloves at delivery, unused, not stretched and at ambient temperature (EN 374). Gloves must be disposed of when the permeation time expires.

After contamination, a change of performance cannot be excluded.
We are not aware of any substances in this product that could cause an allergic reaction.

Disposal The gloves should be disposed of properly as household waste. If they come into contact with chemicals, please consult the chemical manufacturer's waste disposal guidelines.

Warning Gloves should not be worn where there is a risk of being caught in moving machinery parts.